

ChemSol

DRILLING FLUID PRODUCTS

FINE SEAL LCM

PRODUCT DESCRIPTION

FINE SEAL is a fine, processed fiber, used as an LCM to plug large loss circulation zones. FINE SEAL is easily blended into the mud system and compliments other LCM materials such as cottonseed hulls and SHELL FILL.

RECOMMENDED TREATMENT

Use as needed for resolving loss of fluid circulation. Treatment levels will vary based on harshness of fluid loss and the type of formation where the losses occur. FINE SEAL can be mixed directly into the mud system without clogging down hole equipment

PRODUCT ADVANTAGES

- Compatible with water based and oil based fluid systems.
- Low cost and beneficial in a variety of formations.
- Easily mixed into the mud system.
- Advantageous when mixed with other LCM products.

TYPICAL CHEMICAL SPECIFICATION AND PROPERTIES

Appearance:	Tan/Brown fibrous material
Flash Point:	NA
Ash %:	2.97%

PRODUCT HANDLING

Review all product specification and MSDS information prior to product application. Utilize chemical handling equipment and personal protection apparel (i.e. goggles & gloves) as specified in product MSDS when handling this material.

STORAGE

Store FINE SEAL in a well ventilated area away from sources of ignition. Avoid contact with moisture.

PACKAGING

FINE SEAL is available in 50lb multi-wall bags.